


SMD MHz Quartz Crystal Resonator

5S-Series (5032)



■ Features

- Size (L x W) 5.0 x 3.2, Height (Max.) 1.2 mm

■ Applications

- Digital Electronics, Consumer Products
- Mobile Communications
- Bluetooth, Wireless LAN



■ General Specifications

#	Items	Parameters
1	Frequency range	8 to 48MHz
2	Oscillation mode	Fundamental
3	Frequency tolerance at 25°C	±10, ±15, ±20, ±30, ±50 ppm
4	Frequency stability Vs. operating temperature range	See below Table 1
5	Equivalent series resistance	See below Table 2
6	Drive level	10, 100, 200 μW or specify
7	Insulation resistance	500 MΩ Min. at DC 100V
8	Load capacitance	8, 10, 12 pF or specify
9	Shunt capacitance (C0)	3 pF Max or specify
10	Aging at 25°C	±3 ppm / year or specify

■ Tab. 1: Frequency Stability Vs. Operating Temperature Range


Temp. \ (ppm)	±15	±20	±50
-40 to +85 °C	●	●	●

Note: The mark "●" denotes our achieved level


■ Tab. 2: Equivalent Series Resistance

Frequency (MHz)	ESR _{MAX} (Ω)	Oscillation mode
8 to 10	60	Fundamental
10 to 20	40	
20 to 40	30	
40 to 48	20	

■ Package Dimensions & Recommended Land Pattern (Unit: mm)



■ Pad Functions



Visit website

EMAIL : yl@dgylec.com
WEB : <http://www.dgylec.com/>
TEL : +86 (0) 769 - 38879888
FAX : +86 (0) 769 - 38879889

